

Kosmalski Herbs & Spices	Specification number	REF-NR:GMP- PII-01/02
Specification	Issue date	31.10.2016
Lick salt Multi Lisal K	Page	1/2

Product name	Lick salt Lisal K
Product no.	LSLK_100
Description	Salt licks are obtained from milled salt by compression of a mixture of minerals containing microelements- magnesium, manganese, zinc, cobalt, iodine, selenium and copper.
Color/appearance	Briquettes are shaped prisms white color with a green tint. Unit weight of 10 ± 0.5 kg.
Taste	Salty, spicy, specific
Usage	Licks are intended for monogastric animals.

Chemical parameters

Quality parameters	Expressed as	Unit	Value
Sodium chloride	NaCl	%	min 92
Humidity	H ₂ O	%	max 1
Insoluble matter in H ₂ O	-	%	max 4
Foreign impurities	-	%	max 0,005%
Magnesium	Mg	g/kg	18
Cobalt	Co	mg/kg	30
Zinc	Zn	mg/kg	1300
Manganese	Mn	mg/kg	1400
Iodine	I	mg/kg	60
Selenium	Se	mg/kg	25
Copper	Cu	mg/kg	150

* Dye - iron oxide

We can produce the mineralized salt licks with a different chemical composition based premix agreed with the client and vet.

Dioxins, heavy metals content The content of undesirable substances in accordance with the Regulation of the Minister of Agriculture and Rural Development on permissible levels of undesirable substances in feed 23.01.2007 Dz.U.2007 No. 18 item 110, as amended.

Biological characteristics The content of impurities of animal origin - zero tolerance. Based on the properties of natural and studies the salt does not raise microbiology.

Physical characteristics No pollution that can cause damage to the gastrointestinal tract of the animal.

Packaging 10 kg briquettes are stored on pallets of 1200 kg or 600 kg. Protected by plastic foil.

Best before date 2 years following production date

Kosmalski Herbs & Spices	Specification number	REF-NR:GMP- PII-01/02
Specification	Issue date	31.10.2016
Lick salt Multi Lisal K	Page	2/2

Storage conditions

Dry warehouses (max 75% relative humidity)

Transport conditions

The product should be transported in clean, indoor means of transport, in accordance with applicable law. The load should be evenly distributed in a manner preventing movement of packs and their mutual damage.

Quality

Lick salt is produced due to following norms:

- PN-EN ISO 9001:2009
- PN-EN ISO 22000:2006
- ZN-97/1:2004